

**William G Search Limited**

Whitehall Road, Leeds, LS12 6EP

Tel: 0116 2639081

Fax: 0113 231 0267

Email: Hire@wgsearch.co.uk or Info@wgsearch.co.uk

Website: www.wgsearch.co.uk or www.searchforhire.co.uk

# SEARCH

## 16' SC Welfare Unit (UKG)



The Mobile 16' Welfare Unit is purpose built for our supplier to meet customers' precise requirements.

It is a secure anti-vandal unit designed to meet the needs of any utility or development project, whilst ensuring compliance with the latest Health and Safety legislation. It ensures that site staff benefit from welfare facilities for the duration of the project.

The structure is a secure fully welded galvatite steel construction, 4.9m x 2.3m in size. It has high security doors with heavy duty hinges and security deadlocks. It also has a side opening window with anti jemmy sliding security shutter, which is locked from within the unit using retaining bolts.

The running gear and chassis with Tandem A1-KO Euro axles allow for greater flexibility in terms of location. It is supplied with a unique removable draw bar system to be stored inside the unit, a wheel clamp and the new Supermule chassis anti-theft arm for additional security.

### Benefits

#### High standard specification / Outstanding value

- Mobility allows for easy relocation
- Peace of mind anti-theft features
- Pleasant daytime facilities support staff morale whilst complying with current Health and Safety legislation
- Easy to clean and maintain interior finish
- Options available maximise efficiency and minimise maintenance
- Versatile/Can be supplied as a static Jack Leg unit

---

**William G Search Limited, Whitehall Road, Leeds, LS12 6EP**  
**Tel: 0113 263 9081; Fax: 0113 2310267; E-mail: hire@wgsearch.co.uk**  
for further details visit our website [www.wgsearch.co.uk](http://www.wgsearch.co.uk) or [www.searchforhire.co.uk](http://www.searchforhire.co.uk)



# 16' SC Welfare Unit (UKG)

## specification

### General Structure

The structure is constructed from 1.25mm I Z Galvanite steel with continuous seam welded joints on a heavy-duty chassis. The flooring is constructed from 15mm exterior grade plywood with polyfloor covering to the topside and galvanised sheet to the underside for durability and protection against fire. The unit is sprayed externally to an average film thickness of 75 microns to customers colour requirements. The walls and ceiling are 12 vinyl faced moisture resistant boarding with water proof rubber seal to the flooring and ventilation to all compartments. Laden weight is between 2250kg & 2400 Kg, depending on generator option.

### Doors, Window & Shutter

3 x high security insulated steel doors with heavy duty hinges and double deadlocks with common keys. Galvanized heavy duty anti-slip steps to all doors. 900mm wide x 1000mm high pvc coated aluminum framed window with top opening. The window has an anti-jemmy sliding security steel shutter operated from within the unit. Double security doors give access to the built-in generator.

### Running Gear and Chassis

Tandem AI-KO Euro axles with sealed-for-life bearings, 3000kg gross weight. 155x12" low profile wheels with spare wheel included. Removable galvanised draw bar to be stored inside drying room. Wheel clamp. Supermule security chassis arm. 4 heavy duty serrated corner steadies with levelling adjustment. Removable road lighting board to be stored inside drying room. Heavy duty serrated jockey wheel and swivel clamp.

### Internal specification

#### Generator

- Europower Super silent diesel 6KVA generator
- Anti-vibration generator mounts
- Sound insulation to generator compartment
- Optional gas conversion or diesel models available

#### Canteen area

- Table and 6 chairs
- Auto-flow hot water system
- Microwave • Kettle
- Soap dispenser • Towel dispenser
- Stainless steel sink and worktop
- Stainless Steel door to water compartment

- Wall cabinet with stainless steel door
- Fire extinguisher
- Waste container • Water container
- Drinking water container
- Cup dispenser
- 2KW wall heater with thermostatic control
- Single 1500mm moisture proof fluorescent light
- Moisture resistant light switch
- Consumer unit with RCD and MCB's with relay operated priority sensing system

#### WC

- Thal re-circulating flush tank toilet, 136 litre capacity

- Sink to wash up to forearm
- Auto-flow hot wash to sink to give 20 seconds flow of water initiated from passive sensor
- Soap dispenser • Towel dispenser
- Toilet roll holder • Bulkhead light
- Water resistant light switch

#### Drying room

- 6 coat hooks
- Tube heater with cover
- Bulkhead light
- Moisture resistant light switch
- Draw bar & lighting board storage
- Tread plate floor and kick board covering



### Options List

- Remote generator start in canteen area • Passive infra-red sensors to activate generator • Frost thermostat to activate generator
- Gas or diesel generators • Hydraulic lowering system • Lighting tower • Can be supplied as jack leg unit with no running gear

**William G Search Limited, Whitehall Road, Leeds, LS12 6EP**  
**Tel: 0113 263 9081; Fax: 0113 2310267; E-mail: hire@wgsearch.co.uk**  
 for further details visit our website [www.wgsearch.co.uk](http://www.wgsearch.co.uk) or [www.searchforhire.co.uk](http://www.searchforhire.co.uk)